



FDA compliant
Series 09

TIGER Drylac® U.S.A., Inc.
1-800-243-8148

WEST COAST (HQ)

1261 East Belmont St.
Ontario, CA 91761
phone 909 930 9100
fax 909 930 9111
customerservicewest@tigerdrylac.com
www.tigerdrylac.com

MIDWEST

3855 Swenson Ave.
St. Charles, IL 60174
phone 630 513 9999
fax 630 513 9998
customerservicemw@tigerdrylac.com

EAST COAST

1100 Commons Blvd.
Reading, PA 19605
phone 610 926 8148
fax 610 926 8149
customerserviceeast@tigerdrylac.com

SOUTHEAST

3400 Town Point Drive NW Ste. 140
Kennesaw, GA 30144
phone 770 218 2490
fax 770 218 2495
customerservicese@tigerdrylac.com

SOUTH

339 Exchange Drive
Arlington, TX 76011
phone 817 277 7995
fax 817 277 1931
customerservicesouth@tigerdrylac.com

**A powder coating for interior applications
compliant to Food and Drugs Administration**
Based on Epoxy / Polyester hybrid

Typical applications

Kitchen surfaces
Food transportation containers
Pharmaceutical handling and storage

Features

- Formulated with raw materials that are compliant with 21 CFR 175.300 (Food and Drugs Administration)

Finish | Colors

- TIGER Drylac® 09/10126
White - smooth glossy 85 - 95*
- TIGER Drylac® 09/80108
Black - smooth glossy 85 - 95*
- TIGER Drylac® 09/70339
Grey - smooth glossy 85 - 95*
- Custom colours are available, however please check for availability of colors due the restrictions in approved raw materials.

For general information please refer to Product data sheet for TIGER Drylac® Series 09 interior applications.

Standard Packaging	55 [lb] / 44 [lb] boxes and 5.0 [lb] Minipack 25 [kg] / 20 [kg] cartons and 2,5 [kg] Minipack
Specific Gravity (ASTM D792)	approx. 1.6 depending on pigmentation
Theoretical Coverage	at specific gravity 1.6 and film thickness of 2.5 [mils] / 60 [µm]: 50.35 [sq ft/lb] / 10.4 [m²/kg] <i>(also please refer to data sheets # 4001 & 4002 in the latest edition)</i>
Storage Stability	6 months at no more than 77 °[F] / 25 °[C]

As a part of our product information program our product data sheets are periodically updated. Therefore, please check our webpage for the latest edition. Our verbal and written recommendations for the use of our products are based upon experience and in accordance with present technological standards. These are given in order to support the buyer or user. They are non-committal and do not create any additional commitments to the purchase agreement. They do not release the buyer from verifying the suitability of our products for the intended application. This product data sheet substitutes any and all previous product data sheet and notes for customers published on this subject matter.